

CYCLE 2025-07

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<<

CN code	TARIC	Reference Mail	Description	Quotas	New or amendment request	Measure status	Partner Position	Public Comments
2909 49 80		8823392/2025	3-Methoxy-3-methyl-1-butanol (CAS RN 56539-66-3); purity by weight 99 % or more	Q/500000kilograms, 01.07-31.12	New	UNDER EXAMINATION	Applicant	Round 2026.07 Surface Cleaners and Liquid Laundry Detergent
2924 19 00		8426547/2025	ADMA 10: N,N-Dimethylcapramide (CAS RN 14433-76-2) with a purity by weight of 95 % or more	Q/2000tonnes, 01.07-31.12	New	UNDER EXAMINATION	Applicant	Round 2026.07 quota request for solvent or co-solvent used for formulating plant protection products (fungicide)
2929 10 00		8738626/2025	Methylene diphenyl diisocyanate (CAS RN 101-68-8); purity by weight 99 % or more	Q/650000kilograms, 01.07-31.12	New	UNDER EXAMINATION	Applicant	Round 2026.07 Elastane for yarn production
2933 39 99		8426856/2025	Fluopyram (ISO) (CAS RN 658066-35-4) with a purity by weight of 96 % or more	Q/75tonnes, 01.07-31.12	New	UNDER EXAMINATION	Applicant	Round 2026.07 Fluopyram, a fungicide used in agriculture
3920 10 89		8426798/2025	Transparent polyolefin elastomer (POE) film: • thickness of not less than 0.44 mm and not more than 0.46 mm, • width of not less than 100 cm and not more than 140	Q/33tonnes, 01.07-31.12	New	UNDER EXAMINATION	Applicant	Round 2026.07 Transparent polyolefin elastomer (POE) film for protecting

			cm, • basis weight of not less than 360 g/m ² and not more than 400 g/m ² , • lamination shrinkage of up to 3 % in the machine direction and up to 1.5 % in the transverse direction, • volume resistivity greater than $1.0 \times 10^{15} \Omega \cdot \text{cm}$, • adhesion to glass greater than 60 N/cm, and • light transmittance above 90 % in the wavelength range of 380 - 1100 nm, for use in the production of photovoltaic cells or modules as the front protective (encapsulation) layer.					photovoltaic modules from external influences
ex 2917 13 90	10	1069948/2012 1151/2007	DE 15.9.2025 new text description: Dimethyl sebacate (CAS RN 106-79-6) with a purity by weight of 97 % or more ----- Dimethyl sebacate (CAS RN 106-79-6)	Q/1000tonnes, 01.07-30.06	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 request for amendment ROUND 2013-07-01: used as intermediate for the production of additives for plastic (light stabilizers) -running quota - 09.2769, 1151/2007, 2917 13 90 10 could be transferred into the Suspension Regulation
ex 2923 90 00	88	1956962/2022	Aqueous solution containing by weight 78 % or more but not more than 82 % of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0)	Q/10000tonnes, 01.07-31.12	Amendment	UNDER EXAMINATION	Applicant	Round 2026/01 request for quota increase Round 2023-01 used in the manufacturer of polymers intended for water treatment
ex 8409 91 00	15	6838521/2024	SE 15.09.2025 Proposed new description Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: - no other components, - a hardness of 90HB or more, - casting defects size of not more than 0,4 mm and not more than 10 defects per cm ² ,	Q/200000pieces, 01.07-30.06	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 amendment request Round 2025/7 used in the manufacture of spark-ignition internal combustion engines for vehicles of tariff heading 8703

			<ul style="list-style-type: none"> - a dendrite arm space in combustion chamber of not more than 25 µm, - a double deck water jacket design, - a weight of 14 kg or more but not more than 19 kg, - a length of 460 mm or more but not more than 510 mm, - a height of 260 mm or more but not more than 286 mm and - a width of 140 mm or more but not more than 150 mm <p>-----</p> <p>Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with:</p> <ul style="list-style-type: none"> - no other components, - a hardness of 52 HRB or more, - casting defects size of not more than 0,4 mm and not more than 10 defects per cm², - a dendrite arm space in combustion chamber of not more than 25 µm, - a double deck water jacket design, - a weight of 14 kg or more but not more than 19 kg, - a length of 506 mm or more but not more than 510 mm, - a height of 282 mm or more but not more than 286 mm and - a width of 143,7 mm or more but not more than 144,3 mm 					
ex 8714 91 10 ex 8714 91 10 ex 8714 91 10	21 31 75	1095094/2012	Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles) (1)	Q/600000pieces, 01.07-31.12	Amendment	UNDER EXAMINATION	Applicant Applicant Applicant Applicant Applicant	Round 2026.07 amendment request ROUND 2013-07-01: A bicycle frame is the supporting construction of the bike. This part connects all the parts of the bike together

2933 99 80		8160198/2025	1-(3-chloropropyl)-1,3-dihydro-2H-benzimidazol-2-one (CAS RN 62780-89-6) with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/01 for use in pharmaceutical industry
2933 99 80		7871687/2025	Allyl (2S,4S)-4-benzoylsulfanyl-2-(dimethylcarbamoyl)pyrrolidine-1-carboxylate (CAS RN 141818-73-7) with a purity by weight of 96 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the pharmaceutical industry
2934 99 90		7873550/2025	(6R,7R)-Benzhydryl 3-hydroxy-8-oxo-7-(2-phenylacetamido)-5-thia-1-azabicyclo [4.2.0] oct-2-ene-2-carboxylate (CAS RN 54639-48-4) with a purity by weight of 95 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		8117043/2025	Benzyl-4-(oxetan-3-yl) piperazine-1-carboxylate (CAS RN 1254115-22-4), with a purity by weight of 99 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		8117362/2025	Adenosine 5'-(trihydrogen diphosphate), 2'-(dihydrogen phosphate), 5',5'-ester with 3-(aminocarbonyl)-1-β-d-ribofuranosylpyridinium hydroxide, inner salt, disodium salt (CAS RN 24292-60-2), with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 for use in the pharmaceutical industry
2934 99 90		7870099/2025	(6R-trans)-7-Amino-8-oxo-3-[[[(1,2,5,6-tetrahydro-2-methyl-5,6-dioxo-1,2,4-triazin-3-yl)thio]methyl]-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 58909-56-1) with a purity by weight of 97 % or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for use in the pharmaceutical industry
3204 17 00		8480717/2025	Colorant C.I. Pigment Violet 23 (CAS RN 215247-95-3) and preparations based on it with a content of colorant C.I. Pigment Violet 23 of 70 % by weight or more	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in pigments preparations
3204 90 00		8824649/2025	Preparation containing by weight of - more than 25 % but not more than 30 % of Oxirane, 2-methyl-, polymer with oxirane, ether with bis(4-(bis(2-	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used for the production of polyurethane

			<p>hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5) and;</p> <ul style="list-style-type: none"> - More than 15 % but not more than 20 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and; - More than 25 % but not more than 30 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2) and; - More than 5 % but not more than 10 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and; - More than 15 % but not more than 20 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) 					
3204 90 00		8823689/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> - more than 90 % but not more than 99 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-(bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) and; - More than 1 % but not more than 10 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used for polyurethane
3204 90 00		8824224/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> - more than 23 % but not more than 36 % of Oxirane, 2-methyl-,polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5) and; 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the manufacture of polyurethane

			<ul style="list-style-type: none"> - More than 4 % but not more than 20 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and; - More than 25 % but not more than 30 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2) and; - More than 5 % but not more than 10 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazenyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and; - More than 15 % but not more than 25 % of Oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) 					
3204 90 00		8823831/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> - More than 5 % but not more than 15 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) and; - More than 85 % but not more than 95 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazenyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the production of polyurethane
3204 90 00		8823937/2025	<p>Preparation containing by weight of</p> <ul style="list-style-type: none"> - more than 40 % but not more than 60 % of Oxirane, 2-methyl-, polymer with oxirane, ether with 2,2-[[3-methyl-4-[(4-methyl-2-benzothiazolyl)azo]phenyl]imino]bis[ethanol] (2:1) (CAS RN 229306-55-2) and; - More than 40 % but not more than 60 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6) 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in production of polyurethane

3204 90 00		8824141/2025	Preparation containing by weight of - more than 50 % but not more than 70 % of Oxirane, methyl-polymer with oxirane, ether with bis(4-[bis(2-hydroxyethyl)amino]phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt block (CAS RN 126042-89-5) and; - More than 30 % but not more than 50 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the manufacture of polyurethane
3204 90 00		8824032/2025	Preparation containing by weight of - more than 60 % but not more than 80 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2',2'',2'''-(sulfonylbis(4,1-phenylene)-2,1-diazenediyl(3-methyl-4,1-phenylene)nitrilo)tetrakis(ethanol) (4:1) (CAS RN 927432-39-1) and; - More than 20 % but not more than 40 % of Polyethylene-polypropylene glycol (CAS RN 9003-11-6)	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the production of polyurethane
3403 11 00		8427256/2025	Lubricating preparation contains by weight - 40 % or more but note more than 60 % silicone (CAS RN: 63394-02-5) - 30 % or more but note more than 50 % hydrocarbon (CAS RN: 308067-53-0) based mineral oils lubricants - 5 % or more but not more than 15 % specialty additives to provide anti-block, cohesive, and antistatic properties, designed specifically for production of spandex fiber	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the spandex yarn industry
3801 10 00		8484406/2025	Artificial graphite, electrically conductive raw material for batteries	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Artificial graphite for batteries
3810 10 00		8495844/2025	Tin or zink based, halide free SMT processing solder paste:	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 used for assembly of electronic systems of a

			<ul style="list-style-type: none"> - with metal contents of 87,5 % or more, but not more than 90,1 % by weight, - with an alloy solidus temperature of 210oC or more, - with a viscosity of 178 Pa·s or more, but not more than 235 Pa·s, - with fines grind of 40 um or less, - with a silver content either of 3,15 % or more, but not more than 3,5 % by weight for tin based paste or of 0,25 % or more, but not more than 0,28 % by weight for zinc based paste, - with or without bismuth content of 2,55 % or more, but not than 2,71 % by weight, - with or without copper content of 0,6 % or more, but not more than 0,7 % by weight 					kind used in automotive industry
3815 12 00		8427494/2025	<p>Catalyst used to obtain paraxylene and orthoxylene by isomerization of methaxylene containing by weight:</p> <ul style="list-style-type: none"> - Aluminium Oxide (CAS RN 1344-28-1) not more than 95 %, - Aluminosilicate (CAS RN 1327-36-2) not more than 15 %, - Platinum (CAS RN 7440-06-4) not more than 2 % - Aluminium Chloride Hydroxide (CAS RN 12042-91-0) not more than 2 % - Hydrogen Sulfide (CAS RN 7783-06-4) not more than 0,2 % 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 used in production of paraxylene and orthoxylene
3815 19 90		8933271/2025	<p>Catalyst for use in the production of acrylonitrile, consisting of a mixture of metal oxides fixed to a silicon dioxide support in powder form, containing 20 % or more but not more than 40 % by weight of molybdenum, bismuth and iron.</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the production of acrylonitrile

3815 19 90		8934646/2025	Catalyst, in the form of powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, with a total content by weight of molybdenum, bismuth and iron of 20 % or more but not more than 50 %, for the preparation in the manufacture of acrylonitrile	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the production of acrylonitrile
3815 90 90		8427437/2025	Catalyst used to remove mercaptans contained in LPG by oxidation, in liquid form, containing by weight; - Complex cobalt components not more than 30 % and water	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026/07 for use in LPG production
3902 90 90		8241545/2025	1-Octene Homopolymer Hydrogenated	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in processed oils
3907 30 00		8675096/2025	Epoxy resin (CAS RN 1675-54-3) containing by weight; - 40 % but not more than 60 % xylene (CAS RN 1330-207-7), - not more than 0,1 % free hydrolyzed sodium chloride (CAS RN 7647-14-5), specially produced for electronic circuits, electrical isolators and coatings	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for electrical insulators and high-voltage-resistant coatings
3907 30 00		8675176/2025	Epoxy resin (CAS RN 1675-54-3) containing by weight - 1 % but not more than 20 % bisphenol (CAS RN 80-05-7), - not more than 0.1 % free hydrolyzable chloride (CAS RN 7647-14-5), - not more than 0.1 % sodium chloride (CAS RN 7647-14-5).	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for use in flexible composite solutions
3907 40 00		8427019/2025	Polycarbonate (CAS RN 235420-85-6) of phosgene and bisphenol A: - containing by weight 12 % or more but not more than 26 % of a copolymer of isophthaloyl chloride, terephthaloyl chloride and resorcinol, - with p-cumylphenol endcaps, and	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to produce pelletized compounds used in various industries

			<ul style="list-style-type: none"> - with a weight average molecular weight (Mw) of 29900 or more but not more than 31900 					
3910 00 00		8495877/2025	<p>Low outgassing thermally conductive silicone paste:</p> <ul style="list-style-type: none"> - with thermal conductivity when cured of 3,45 W/(m· K) or more but not more than 3,55 W/(m· K), - with continuous use temperature range between -60 °C and 200 °C or more, - with heat capacity when cured of 0,75 J/g·K or more but not more than 0,85 J/g·K, - with volume resistivity when cured of 1010 Ω·m or more, - packaged in containers of 30 kg or bigger 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in PCBs for cooling devices
3919 90 80		8329858/2025	<p>Self-adhesive plastic plate, printed, also shaped:made of polycarbonate film type Makrofol DE 1-4,</p> <ul style="list-style-type: none"> - with a thickness of 0.3 mm or more, but not more than 0.4 mm, - with minimal dimensions 63 mm x 15 mm - with maximum dimensions 278 mm x 117 mm - with a weight of not more than exceeding 5 g per piece, <p>intended for integration into combined instrument panels of passenger cars</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for use in passenger cars panels
3920 62 19		8495754/2025	<p>High-performance print grade of poly(ethylene terephthalate) (PET) film in rolls with:</p> <ul style="list-style-type: none"> - a thickness of 35 µm or more, but not more than 75 µm, 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the production of shrink sleeve labels

			<ul style="list-style-type: none"> - a tensile strength of at least 40 MPa in the machine direction (MD) and at least 200 MPa in the transverse direction (TD), - an elongation at break of at least 400 % in MD and at least 30 % in TD, - a heat shrinkage (at 90 degrees Celsius for 10 seconds) in MD of 0,49 % or more, but not more than 0,51 %, - a heat shrinkage dynamic in TD of no more than 20 percentage points between 55°C and 70°C, - a light transmittance equal to or greater than 85 %, - a haze ratio equal to or less than 6 %, - a surface tension equal to or greater than 38 mN/m, - with a density of 1.30 g/cm³ or more, but not more than 1.34 g/cm³, - a shelf life declared by the manufacturer of not less than 12 months 					
3921 19 00		8480639/2025	<p>Thermal Runaway Protection Pads,</p> <ul style="list-style-type: none"> - made from closed-cell silicone foam, - with a thickness of 2.0 mm or more but not more than 4.8 mm, - a thermal insulation of 0.33 Km²/W (according to ASTM-C518) - a dielectric strength of 3.4 Kv/mm (according to ASTM- D149) 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for battery cells
3921 90 55		8480332/2025	<p>Flexible prepreg sheets or rolls made of modified epoxy resin without the use of halogenated flame retardants with embedded glass fabric</p> <ul style="list-style-type: none"> - with a TG >145°C and < 200° according to TMA - with a classification according to IPC-4101/128 or 4101/130 or IPC-4101/153 or 4101/154 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the production of printed circuit boards

5401 10 14		8377501/2025	<p>Poly/poly core-spun yarns made from polyester high tenacity filament yarn as a core:</p> <ul style="list-style-type: none"> - covered with the staple polyester fibres, - with a twist of 410 TPM or more, but not more than 1200 TPM, - with a linear density of 200 dtex or more, but not more than 1500 dtex, - with an average minimum tenacity of 46 cN/tex, - with an elongation of 13 % or more, but not more than 23 %, - wound on the perforated dyeing tube ready for dyeing, - with a weight including the tube of 900 g or more 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 for the production of polyester threads
5402 20 00		8377465/2025	<p>High tenacity polyester filament yarn:</p> <ul style="list-style-type: none"> - with final twist of Z direction, - with a linear density of 100 dtex or more, but not more than 4000 dtex, - with an average minimum tenacity of 64 cN/tex, - with an elongation of 12 % or more, but not more than 28 %, - with a shrinkage in 98oC of 0 % or more, but not more than 3,5 %, - wound on the perforated dyeing tube ready for dyeing 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 used in threads for furniture manufacturing
5503 90 00		8669165/2025	<p>Staple fibres fully encapsulated by polyethylene sheath with PET core with:</p> <ul style="list-style-type: none"> - a linear density of 0,60 dtex or more, but not more than 1,99 dtex, - a staple length of 37 mm or more, but not more than 44 mm, - an elongation at break equal to or greater than 80 %, - a minimum tenacity of 1 cN/dtex 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 used in the industry of hygiene products

6804 21 00		8446586/2025	<p>Wheels suitable for grinding, rounding, polishing, aligning or cutting:</p> <ul style="list-style-type: none"> - of natural or synthetic diamonds which are agglomerated with metal, metal alloy, glass, ceramic, or resin, - whether or not containing a hole in the centre, - with an external diameter not more than 870 mm, <p>of a kind used for machines for the manufacture of semiconductor wafers.</p> <p>(1)</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the industry of semiconductor wafers
6814 10 00		8241393/2025	<p>Phlogopite Mica Tape bonded to reinforced material of non-alkaline glass fabric or polyethylene film with high temperature resistant silicone resin,</p> <ul style="list-style-type: none"> - with a thickness of 0.10mm (+0.015mm) or more but not more than 16mm, - with a width of 500mm or more but not more than 1200mm, a mica content of 80g/m² (+3 g/m²) but not more than 165 g/m², - a tensile strength of 110N/cm or more but not more than 130N/cm 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used for fire resistant wire and cable
6814 90 00		8484277/2025	<p>Li-ion battery module component made of mica (MICA) for fire protection, with a specially designed shape for the top and sides</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Li-ion battery module component made of mica for fire protection
7002 20 90		8495786/2025	<p>Glass preforms made of high-purity silica (quartz) glass with an optical core made of germanium-doped silica (quartz) glass, intended for the production of low-loss optical fiber:</p> <ul style="list-style-type: none"> - 90 % of all preforms preforms weigh between 46 kg and 50 kg, with an average weight of 46,2 kg, 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 to be used in the production of optical fiber

			<ul style="list-style-type: none"> - the maximum length of the preform is 2500 mm, - diameter of the preform ranges between 115 mm and 139 mm, with the average diameter of 127 mm, - the preforms contain a handle with a diameter of 25,4 mm, coated at the end with aluminum oxide, allowing the preform to be suspended in the preform holder of the optical fiber manufacturing device 					
7115 90 00		8427632/2025	A paste used in solar cell production containing 80-95 % Silver Powder, 1-10 % Isobutyric acid, 0.1-1 % Fatty acid salts of Polyamide by weight	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 used in solar cell production
8110 90 00		8426962/2025	Antimony-Beryllium pellets containing by weight : <ul style="list-style-type: none"> - 20 % or more but not more than 25 % of beryllium (CAS 7440-41-7) - 77 % or more but not more than 83 % of antimony (CAS 7440-36-0) 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.7 used in nuclear power plant
8409 91 00		8329795/2025	The exhaust gas recirculation assembly consisting of: <ul style="list-style-type: none"> - a control unit, - an air throttle, - an intake pipe, - an outlet hose, for use in the manufacture of spark-ignition piston internal combustion engines of motor vehicles (1)	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 The exhaust gas recirculation assembly for use in the manufacture of combustion engines of motor vehicles
8414 30 20		8426646/2025	Hermetic compressor for R600a refrigerant for the production of refrigerators and freezers; <ul style="list-style-type: none"> - with a power not exceeding 0,4 kW, - pre filled with lubricant from 130 ml to 180 ml, - suction and processing pipe inner diameter from 6.10 mm to 6.60 mm, 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 compressor for production of refrigerators and freezers

			<ul style="list-style-type: none"> - discharge pipe inner diameter from 4.80 mm to 5.00 mm, - driven by AC electric motor, - cooling capacity from 137 to 184 W at 3000 rpm, - displacement from 7.5 cm³ to 10.5 cm³. <p>(1)</p>					
8414 30 20		8495675/2025	Refrigeration compressor for R-600a as refrigerant with: <ul style="list-style-type: none"> - pre-charged with the mineral lubricant oil with oil charge 180 cm³ or more, but not more than 220 cm³, - with a brushless DC electric motor (BLDC), - without inverter controller, - weight of 6,2 kg or more, but not more than 6,8 kg, - with aluminium or copper motor winding, - with left side injection from suction line, - with displacement 5 cm³ or more, but not more than 8,8 cm³, - speed of 1020 rpm or more, but not more than 4 800 rpm, - with an output power of 5 W or more, but not more than 300 W 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Refrigeration compressor
8414 59 35		8669363/2025	DC motor centrifugal fans with: • a nominal voltage of 8 V or more, but not more than 13 V, • a nominal max speed of 1400 rpm or more, but not more than 1950 rpm, • a horizontal or vertical shaft position of fan blades, • boosting time of 10 seconds or less, • a cable with RAST 2,5 connector of length of 30 cm or more, but not more than 50 cm, • a nominal power of 0,7 W or more, but not more than 3,5 W, • with tachometer or feedback signal to monitor the speed RAST = Raster-Anschluss-Steck-Technik	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 DC motor centrifugal fans for refrigerator

8418 99 90		8669318/2025	<p>Condenser being a type of heat exchanger made entirely of aluminum A3102 / A3003 / A4045 / A4343, consisting of two vertical pipes, including one with inlet and outlet tubes, and 16 arranged horizontally and in parallel, flat tubes with placed fins between them, with:</p> <ul style="list-style-type: none"> - a width of 297 mm or more, but not more than 373 mm, - a height of 154 mm or more but not more than 158 mm, - a depth of 17 mm or more but not more than 23 mm, - a flatness smaller than 2 mm, - a weight of 224g or more, but not more than 283 g 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Condenser used in refrigerator
8483 20 00		8484102/2025	<p>Commutator End Shield for the starter motors of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-46000 or EN AC-46000 S, according to the DIN EN 1706 standard; • without bearing</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Commutator End Shield for the starter motors of passenger cars and commercial vehicles
8483 50 80		8627782/2025	<p>Metal spun single or double pulley:</p> <ul style="list-style-type: none"> - made of DC03 steel or similar non alloy steel or free cutting steel, - with a pitch diameter of 67 mm or more but not more than 145 mm, - with an inner hole designed for bearing mounting or key mounting 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Metal spun single or double pulley for manufacturing gardening tools and machinery
8483 50 80		8627698/2025	<p>Metal spun triple pulley:</p> <ul style="list-style-type: none"> - made of DC03 steel or similar non-alloy steel or free cutting steel, - with a pitch diameter of 60 mm or more, but not more than 130 mm, - with an inner hole designed for bearing mounting 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Metal spun triple pulley for manufacturing gardening tools and machinery

8483 60 80		8484181/2025	Overrunning clutch for passenger car and commercial vehicle starter motors • with total length of at least 49.4 mm but not more than 210 mm; • tooth number of starting-motor pinion: at least 9 but not more than 16 pieces	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Overrunning clutch for passenger car and commercial vehicle starter motors
8501 32 00		8621903/2025	Electric Permanent Magnet Synchronous Motor with: <ul style="list-style-type: none"> - a rotor containing 8 poles generated by permanent magnets composed mainly with praseodymium-neodymium-iron-boron (per GB/T 13560-2017 standard) enclosed in stainless steel cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more, but no more than 10,007 mm, - a motor terminals located across the radius 37,00 mm and separated by an angle of 30,00 °, - a motor housing made of ADC12 (EN AC46000) aluminum alloy die casting with composition of aluminum-silicon-copper (per JIS H5302-2000 or EN 1706 standard), - a back electromotive force constant (Ke) of 0,0265 V-sec/rad or more, but no more than 0,0293 V-sec/rad, - a back electromotive force harmonic order: 5th no more than 0,4 % (of fundamental) and 7th no more than 0,2 % (of fundamental), - a synchronous inductance of 33,49 μH or more, but no more than 37,01 μH, - a cogging torque of no more than 15 mNm, - a friction torque in ambient temperature of no more than 20 mNm, - a maximum temperature of motor operation of no more than 200 °C 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Electric permanent magnet synchronous motor for manufacture of the electric power steering system in a motor vehicle

8503 00 20		8483412/2025	Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles:• with an outer diameter of at least 90 mm but not more than 120 mm,• with an inner diameter of at least 65 mm but not more than 80 mm,• with a height of at least 30 mm but not more than 45 mm,• with a weight of at least 0,7 kg but not more than 1,2 kg.	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles
8503 00 20		8483954/2025	Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles: • with an outer diameter of at least 65 mm but not more than 80 mm, • with an inner diameter of at least 15 mm but not more than 25 mm, • with a height of at least 30 mm but not more than 45 mm, • with a weight of at least 0,5 kg but not more than 0,8 kg.	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles
8503 00 98		8484022/2025	Armature for the starter motors of passenger cars and commercial vehicles - with an outer diameter of at least 52 mm but not more than 80 mm; - with a commutator copper wire diameter of at least 2 mm but not more than 4 mm	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Armature for the starter motors of passenger cars and commercial vehicles
8511 90 00		8484229/2025	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-47100 or EN AC-47100 S or EN AC-46000 or EN AC-46000 S or EN AC-44300 according to DIN EN 1706 standard; • without bearing	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Drive end shield for starter motors and alternators of passenger cars and commercial vehicles
8511 90 00		8484137/2025	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles • produced with high pressure precision die casting technology; • made of aluminium alloy with numerical designation EN AC-47100 or EN AC-47100 S or EN AC-46000 or EN AC-46000 S or	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Drive end shield for starter motors and alternators of passenger cars and commercial vehicles

			EN AC-44300 according to DIN EN 1706 standards; • with bearing					
8511 90 00		8484067/2025	Commutator for passenger car and commercial vehicle starter motors • with a length of at least 27.7 mm but not more than 44.6 mm; • with umbrella or drum design	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Commutator for passenger car and commercial vehicle starter motors
8516 80 80		8669241/2025	Electric heating resistor with a triple loop design, intended for heating water in automatic household washing machines: <ul style="list-style-type: none"> - mainly made of AISI 316L stainless steel, - with a rated voltage of 230V, - with a rated power of 2000W, - with a total heating element length of 217 mm or more, but not more than 223 mm, - with a working length of the heating element of 169,5 mm or more, but not more than 174,5 mm, - with a mounting flange diameter of 28 mm or more, but not more than 32 mm, - with a heating element bending radius of 10,75 mm, - equipped with thermal fuses, - without a built-in NTC sensor, - with nickel plated terminal pin and connector 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Electric heating resistor with a triple loop design, intended for heating water in automatic household washing machines
8538 90 99		8627835/2025	Controller covers made of aluminum AlSi9Cu alloy (EN AC-46000) with: <ul style="list-style-type: none"> - heat radiating functionality, - a volume as-cast lower than 128 000 mm³, - a volume machined lower than 126 000 mm³, - a length and width of 130 mm or lower, - a height of 40 mm or lower, - a wall thickness of 2,5 mm or more but no more than 16 mm, 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Controller covers for manufacturing of the automotive steering systems

			<ul style="list-style-type: none"> - a 6 to 20 mounting screw holes diameter 2,5 mm or more, but no more than 4,0 mm and tolerance for diameter required as 0,05 mm, - with critical assembly areas where flatness is defined as of 0,1 mm, - tolerance machining of 0,05 mm or lower diameter tolerance and flatness of 0,1 mm or lower 					
8544 30 00		8329599/2025	<p>High voltage battery cable assembly comprising at least:</p> <ul style="list-style-type: none"> - single core high voltage cable terminated with a flat lug, - safety fuse for an electric current of 10 A or more but not more than 400 A, - flat copper conductor with surface insulation, - three or more plastic clips for attachment for use in the production of rechargeable batteries for hybrid and electric vehicles <p>(1)</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 The high-voltage battery cable assembly used for connecting battery cell assemblies
8544 30 00		8329746/2025	<p>High-voltage single-core battery supply cable comprising at least:</p> <ul style="list-style-type: none"> - a high-voltage connector, - a metal flat lug with an eyelet in a plastic housing, - three or more plastic mounting clips for use in the production of rechargeable batteries for hybrid and electric vehicles <p>(1)</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 High-voltage battery supply cable for the positive pole
8544 30 00		8329712/2025	<p>A wiring harness for transmitting safety parameters from battery modules comprising at least:</p> <ul style="list-style-type: none"> - input and output connectors, - three or more plastic mounting clips for use in the production of rechargeable batteries for hybrid and electric vehicles 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 A wiring harness for use in the production of rechargeable batteries for hybrid and electric vehicles

			(1)					
8544 42 90		8669200/2025	<p>Wire harness for power supply connection to printed board assembly (PBA):</p> <ul style="list-style-type: none"> - with connectors used in electrical components of rider frontmowers, hedge Trimmers, chainsaws, brushcutters, blowers and Li-Ion Batteries, - composed of wires with crimped wire-to-board connectors, - bundled with rubber, vinyl, electrical tape, conduit, a weave of extruded string or a combination of thereof, - for the transmission of signals and/or electrical power 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Wire harness for power supply connection to printed board assembly (PBA)
8548 00 90		8627638/2025	<p>An Electromagnetic Interference (EMI) filter designed to eliminate conducted electromagnetic interference from the power line, mounted at the power input of automatic washing machines:</p> <ul style="list-style-type: none"> - Rated voltage: 250 V AC - Rated current: no more than 15 A - Operating frequency: 50/60 Hz - Dielectric strength: 1500V AC for 1 minute - Containing a bleeder resistor with a resistance of 470 kΩ - Containing three varistors for rated voltage equal to 681V, 910V and 1800V - Mounted with an M8 screw with an average breaking force of 93 kgf/cm 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 An Electromagnetic Interference (EMI) filter for production of the automatic washing machines
8708 94 99		8621762/2025	<p>Assist pinion made of carbon steel alloy steel per ISO BG/T 3077, 20CrMo, with:</p> <ul style="list-style-type: none"> - a carburized part surface, - a surface hardness of 58 HRC or more, but no more than 63 HRC (per Hardness Rockwell scale C), 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Assist pinion for manufacture of the vehicle steering systems

			<ul style="list-style-type: none"> - a length of 113,15 mm or more but not more than 113,85 mm, - an outer diameter of 21,7 mm or more, but not more than 21,8 mm, - 7 teeth, - a knurling on an outer surface of major diameter 27,98 mm or more but not more than 28,08 mm 					
8708 94 99		8621740/2025	<p>Blank Asm worm gear consisting of hub made of carbon steel (per GB/T 699 grade 25 or DIN EN 10277 grade 11 SMn 30) and ring made of cast polyamide 6/12 with:</p> <ul style="list-style-type: none"> - an outer diameter of 97,35 mm or more, but not more than 102,65 mm, - an inner diameter of 27,91 mm or more, but not more than 27,93 mm, - a height of the Hub of 11,75 mm or more, but not more than 12,00 mm, - an overall height of 16,00 mm or more, but not more than 18,00 mm 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Blank Asm worm gear for manufacture of the steering gearboxes for vehicle control systems
8708 94 99		8621785/2025	<p>Steering rack made of carbon steel JIS G 4051 S45C Modified Steel with:</p> <ul style="list-style-type: none"> - a minimal yield strength of 690 MPa, - an induction harden tooth section and back side of the rack teeth with hardness of 54 HRC or more, but no more than 60 HRC (per Hardness Rockwell scale C), - a maximum length of 666,55 mm or more but not more than 667,05mm, - an outer diameter of 25,944 mm or more, but not more than 28 mm, - a 31 teeth on rack assist side and 30 teeth on rack handweel side, - M14 internal threads on both ends 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Steering rack for manufacture of the vehicle steering systems

8708 94 99		8495929/2025	<p>Inner tie rod made with SCM440 JIS G 4053 steel designed for mounting to the vehicle knuckle and steering rack, with:</p> <ul style="list-style-type: none"> - a housing made with GB/T699 grade 20 steel, - a ball seat made of polyoxymethylene plastic, - a diameter of tie rod housing equal to 41.00 mm, - a distance from the end of tie rod to plane facing rack steering of 205,6 mm, 213,6 mm, or 233,6 mm, - a thread connecting outer tie rod and inner tie rod, with dimensions of M14 x 1.5 G, - a ball stud mounted to the end of tie rod with distance of 184,2 mm or more, but no more than 213,8 mm, - lubricant - for use in the manufacture of vehicle's steering system 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Inner tie rod used in the manufacture of vehicle's steering system
8708 94 99		8621855/2025	<p>Steering pinion made of carbon steel alloy steel (per JIS G4052 GRADE SCM415H) with:</p> <ul style="list-style-type: none"> - a carburized surface with an exception of t-bar hole, - a surface hardness of 58 HRC or more but not more than 63 HRC (per Hardness Rockwell scale C), - a length of 143,08 mm or more but not more than 143,78 mm, - an outer diameter of 26,65 mm or more, but not more than 28,05 mm, - with pinion of 10 or 11 teeth, - an inner diameter of 6,55 mm or more but not more than 6,70 mm 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Steering pinion for manufacture of the vehicle steering systems
8708 99 97		8495712/2025	<p>Inner pole electromagnet core used in MR (Magneto-Rheological) engine mount to reduce</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Inner pole electromagnet

			<p>shocks, and for isolation and damping in passenger cars, with:</p> <ul style="list-style-type: none"> - a maximum diameter of 90,95 mm, - an overall height of 24,5mm, - powder metal assembly, - an impregnated with sealant, - a zinc plated 					core used in MR (Magneto-Rheological) engine mounts used in automotive applications.
8708 99 97		8495981/2025	<p>Outer tie rod with a housing made with of 40Cr GB/T 3077 steel, with:</p> <ul style="list-style-type: none"> - a ball stud made of E6SCM440 JIS G 4053 steel, - a ball seat made of polyoxymethylene plastic, - a distance between the end of the threaded hole and the centre of the ball stud of 213,00 mm, - a ball stud diameter of 25,00 mm, - with a threaded hole depth of 47,5 mm, with dimensions of M14 x 1,5, - a boot seal, - a boot seal protector and retaining ring, - lubricant <p>for use in the manufacture of vehicle's steering system</p>	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Outer tie rod for use in the manufacture of vehicle's steering system
9401 99 20		8495825/2025	<p>Latch seat system modules enabling seat sliding, latching and unlatching in random, independent positions along the rails:</p> <ul style="list-style-type: none"> - with an integrated safety locking mechanism, - with a cassette architecture for integration with seat through screw connections, - with an anti-noise system, - interfacing with car rail systems, - without electronic control unit, - without semiconductors, - with a weight of 1475 g or more but not more than 1619 g 	<u>S</u>	New	UNDER EXAMINATION	Applicant	Round 2026.07 Latch seat system modules enabling seat sliding in motor vehicles

ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 10 ex 1513 29 30	20 20 20 20 20 20	1/1/1999 PROLONG 2022 PROLONG 2025	DE 15.09.2025 new text description: Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: - industrial monocarboxylic fatty acids of subheading 3823 19 10, - methyl esters of fatty acids of heading 2915 or 2916, - fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the preparation of cosmetics, washing products or pharmaceutical products, - fatty alcohols of subheading 2905 16, pure or mixed, for the preparation of cosmetics, washing products or pharmaceutical products, - stearic acid of subheading 3823 11 00, - goods of heading 3401, or - fatty acids with high purity of heading 2915 ----- Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: - industrial monocarboxylic fatty acids of subheading 3823 19 10, - methyl esters of fatty acids of heading 2915 or 2916, - fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, - fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, - stearic acid of subheading 3823 11 00, - goods of heading 3401, or - fatty acids with high purity of heading 2915 (1)	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant Applicant Applicant Applicant Applicant Applicant	Round 2026.07 Amendment request
ex 1515 90 99	92	1959/1/2002	Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 %	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 Review of the measure

		<p>PROLONG 2019 PROLONG 2024 PROLONG 2025</p>	<p>of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid</p>				Applicant	<p>Ingredient to manufacture infant formula nutritional products arachidonic acid = icoso-5,8,11,14-tetraenoic acid = cis,cis,cis,cis-5,8,11,14-icosatetraenoic acid docosahexaenoic acid = doconexent (INN) = cis-4,7,10,13,16,19-docosahexaenoic acid</p>
<p>ex 1517 90 99 1518 00 99</p>	30	<p>833/06 PROLONG 2022</p>	<p>NL 03.07.2025 For the ARA products (suspension): Vegetable and/or microbial oil, refined, containing by weight: - 25 % or more but not more than 70 % arachidonic acid - not more than 5 % docosahexenoic acid, standardized with vegetable oil and For the EPA/DHA products (quota): Vegetable and/or microbial oil, refined, containing by weight: - 10 % or more but not more than 80 % of eicosapentaenoic acid - a minimum eicosapentaenoic acid/(eicosapentaenoic acid + docosahexenoic acid) ratio of more than 20 %, standardized with vegetable oil --- FR 14.05.2025 (supported by BG 16.05) Vegetable and/or microbial oil, refined, containing by weight: - 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexaenoic acid</p>	<u>S</u>	Amendme nt	<p>UNDER EXAMINATION</p>	<p>Applicant Applicant Applicant Applicant Applicant Applicant</p>	<p>Round 2026-01- request for amendment.// trade names : DHA and ARA oils (Arasco & Dhasco)</p>

			<p>standardized with vegetable oil --- NL new proposal: Vegetable and/or microbial oil, whether or not refined, containing by weight:</p> <ul style="list-style-type: none"> - 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid, or - 10 % or more but not more than 80 % of eicosapentaenoic acid and a minimum ratio of EPA/(EPA+DHA) over 20 %, standardized with vegetable oil <p>*** Current description: Vegetable and/or microbial oil, refined, containing by weight:</p> <ul style="list-style-type: none"> - 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid, or - 10 % or more but not more than 80 % of eicosapentaenoic acid and a minimum ratio of EPA/(EPA+DHA) over 20 %, standardized with vegetable oil 					
ex 2835 10 00	20	3058712/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>DE 15.9.2025 new text description: Sodium hypophosphite (CAS RN 7681-53-0) with a purity by weight of 97 % or more or as aqueous solution containing by weight 55 % or more but not more than 65 % ----- Sodium hypophosphite (CAS RN 7681-53-0)</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 request for amendment ROUND 2014-07-01 intended use: Incorporation in the formulations of chemical plating and/or raw material for flame retardant
ex 2841 70 00	30	2996043/2014 PROLONG 2020 PROLONG 2025	<p>DE 15.9.2025 requested amended description: Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) with a purity by weight of 98 % or more -----</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request ROUND 2015-07 Product used for production of hydrodesulfurisation catalysts

			Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2)					
ex 2842 10 00	60	1345815/2016	NL 15.09.2025 Requested new description: Aluminosilicate (CAS RN 1318-02-1) with - a purity by weight of 94 % or more, - a zeolite structure of aluminophosphate-eighteen (AEI), and - a phase purity of 90 % or more for use in the manufacture of copper zeolite or washcoat used in the automotive catalyst production ----- Aluminosilicate (CAS RN 1318-02-1) with - a purity by weight of 94 % or more, - a zeolite structure of aluminophosphate-eighteen (AEI), and - a phase purity of 90 % or more for use in the manufacture of copper zeolite (1)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant Applicant	Round 2026.07 Amendment request ROUND 2017-01 Component will be used in the manufacture of automotive catalyst
ex 2903 99 80	50	1289/2008 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: Fluorobenzene (CAS RN 462-06-6) with a purity by weight of 99 % or more ----- Fluorobenzene (CAS RN 462-06-6)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant Applicant	Round 2026.07 Amendment request
ex 2904 99 00	80	3078740/2014 3078765/2014 PROLONG 2020 PROLONG 2025	DE 15.9.2025 requested amended description: 1-Chloro-2-nitrobenzene (CAS RN 88-73-3) with a purity by weight of 99 % or more ----- 1-Chloro-2-nitrobenzene (CAS RN 88-73-3)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant Applicant	Round 2026/07 amendment request End-use: Used in the paints industry and the printing inks industry, for pigment preparation
ex 2906 19 00	50	555842/2014 PROLONG 2020 PROLONG 2025	4-tert-Butylcyclohexanol (CAS RN 98-52-2)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request ROUND 2015-01-01 4-tert-Butylcyclohexanol is

									used in the manufacture of p-tert-Butylcyclohexyl chloroformate (CAS RN 42125-46-2).
ex 2914 19 90	30	1046/2007 PROLONG 2023	DE 15.9.2025 requested amended description: 3-Methylbutanone (CAS RN 563-80-4) with a purity by weight of 97 % or more ----- 3-Methylbutanone (CAS RN 563-80-4)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request alternative name : isopropylmethylketone	
ex 2914 39 00	30	1013/2007 PROLONG 2023	DE 15.9.2025 new text description: Benzophenone (CAS RN 119-61-9) with a purity by weight of 99 % or more ----- Benzophenone (CAS RN 119-61-9)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 request for amendment trade name : BZQ	
ex 2918 29 00	50	1301/3/1994 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.9.2025 requested amended description: Hexamethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2) with a purity by weight of 97 % or more ----- Hexamethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request 1,6-Hexandiobis-3-(3,5-di-tert-butyl-4-hydroxyphenyl)propion at	
ex 2921 42 00	35	847/05 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.9.2025 requested amended description: 2-Nitroaniline (CAS RN 88-74-4) with a purity by weight of 99 % or more ----- 2-Nitroaniline (CAS RN 88-74-4)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request	
ex 2921 49 00	40	1996/1/2001 PROLONG 2019 PROLONG 2024 PROLONG 2025	15.9.2025 DE requested amended description: N-1-Naphthylaniline (CAS RN 90-30-2) with a purity by weight of 98 % or more ----- N-1-Naphthylaniline (CAS RN 90-30-2)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 amendment request	

ex 2924 19 00	60	975/06 PROLONG 2022	DE 15.09.2025 Requested amended description: N,N-Dimethylacrylamide (CAS RN 2680-03-7) with a purity by weight of 97 % or more ----- N,N-Dimethylacrylamide (CAS RN 2680-03-7)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request short name : DMAA
ex 2924 29 70	17	662655/2014 PROLONG 2020 PROLONG 2025	DE 15.09.2025 Requested amended description: 2-(Trifluormethyl)benzamid (CAS RN 360-64-5) with a purity by weight of 98 % or more ----- 2-(Trifluormethyl)benzamid (CAS RN 360-64-5)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request ROUND 2015-01-01 Manufacture of a plant protection product // Fungicide (protection of plants from fungal attack)
ex 2925 11 00	30	462/2/1985 PROLONG 2019 PROLONG 2024 PROLONG 2025	1,2-benzisothiazol-3(2H)-one 1,1-dioxide (CAS RN 81-07-2) or sodium 1,2-benzothiazol-3-olate 1,1-dioxide (CAS RN 128-44-9) with a purity by weight of 98 % or more	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request
ex 2928 00 90	10	446/1/1981 PROLONG 2019 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: 3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'- bipropionamide (CAS RN 32687-78-8) with a purity by weight of 97 % or more ----- 3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'- bipropionamide (CAS RN 32687-78-8)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request
ex 2928 00 90	55	311617/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025	Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1)	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 Amendment request ROUND 2014-01-01 >> Commercial denomination: Amino guanidine bicarbonate >> End-use: organic intermediate product for the manufacture of pigments

ex 2933 69 80	45	1286961/2018 PROLONG 2024 PROLONG 2025	DE 15.09.2025 Requested amended description: 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) with a purity by weight of 98 % or more ----- 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6)	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 Amendment request ROUND 2019-01 This substance is used in the following products: polymers e in particular building materials, agricultural films, adhesives and sealants, coating products and cosmetics and personal care products
ex 2934 99 90	25	130914/2010 PROLONG 2016 PROLONG 2021	NL 15.09.2025 Requested amended description 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8) with a purity by weight of 97 % or more ----- 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request
ex 2935 90 90	56	3702997/2015 PROLONG 2021	N-(p-Toluenesulphonyl)-N'-(3-(p-toluenesulphonyloxy)phenyl)urea (CAS RN 232938-43-1)	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026/07 review of the suspension ROUND 201607 Phenol-free color developer for thermal paper
ex 3204 15 00	25	6633361/2024	Mixture in a 3:2 ratio of colourants C.I. Vat Blue 1 potassium salt (CAS RN 835912-68-0) and C.I. VAT Blue 1 sodium salt (CAS RN 894-86-0) and preparations based thereon with a combined content of colourants C.I. Vat Blue 1 salts of 40 % or more by weight	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 - Objection Round 2025/7 - for use in the textile industry
ex 3809 91 00	20	6559753/2024	TR 15.09.2025 Requested amended description: Aqueous antimony pentoxide mixture containing by weight: • 46 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9) • 1 % or more but not more than 10 % of triethanolamine (CAS RN 102-71-6) or 1 % or	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request 2025/7 - Flame retardant to be used in modacrylic fiber

			<p>more but not more than 10 % of triethanolamine phosphate (CAS RN 10017-58-6)</p> <p>-----</p> <p>Aqueous antimony pentoxide mixture containing by weight:</p> <ul style="list-style-type: none"> - 48 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), - 1 % or more but not more than 5 % of triethanolamine (CAS RN 102-71-6) 					
ex 3811 21 00 3811 90 00	10	596/6/1987 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>NL 15.09.2025 Amended description: Solution of mineral oils (CAS RN 64742-52-5, 64742-53-6, 64742-56-9 or blends thereof) containing by weight:</p> <ul style="list-style-type: none"> - 25 % or more but not more than 55 % of the barium, calcium, magnesium or zinc salt of dinonylnaphthylsulphonic acid (CAS RN 25619-56-1, 28015-99-8, 28016-00-4, or 57855-77-3) - whether or not, not more than 25 % of the barium, calcium, magnesium or zinc salt of a mixture of C3-C24 carboxylic acids (CAS RN 68990-37-4) <p>-----</p> <p>Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment and double classification request
ex 3815 12 00	10	1023/1/1980 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>DE 15.09.2025 Requested amended description: Catalyst in the form of granules, wheels or ring-shaped structures</p> <ul style="list-style-type: none"> - of a diameter of 3 mm or more, but not exceeding 10 mm, - containing 8 % or more but not more than 40 % by weight of silver - on a carrier based on aluminium oxide, - with one or more promoters <p>-----</p> <p>Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 Amendment request

			oxide support and containing by weight 8 % or more but not more than 40 % of silver					
ex 3815 90 90	80	279/4/1996 PROLONG 2015 PROLONG 2016 PROLONG 2021	NL 15.9.2025 new text description: Catalyst in isobutanol (CAS RN 78-83-1), containing by weight: - 50 % or more but not more than 65 % of dinonylnaphthalenedisulphonic acid (CAS RN 60223-95-2) ----- Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026/07 request for amendment
ex 3906 90 90	33	1138473/2015 PROLONG 2021	New text proposal: Mixture containing by weight: - 80 % but not more than 90 % of Core shell polymer of butyl acrylate, ethyl acrylate, methyl-acrylate and allyl methacrylate (CAS RN 73026-23-0) and - 10 % but not more than 20 % of copolymer of methyl methacrylate and ethyl acrylate (CAS RN 9010-88-2) -- Old text: Core shell copolymer of butyl acrylate and alkyl methacrylate, with a particle size of 5 µm or more but not more than 10 µm	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant	Round 2026.7 Request for amendment ROUND 01- 2016:incorporation in thermoplastics extrusion process
ex 3919 90 80	51	1702/16/2002/v2 PROLONG 2019 PROLONG 2024 PROLONG 2025	NL 15.09.2025 Amended description: Biaxially- oriented film of poly(methyl methacrylate), of a thickness of 20 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet ----- Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, covered on one side with an adhesive layer and a release sheet	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 Amendment request

ex 3926 90 97	77	5560026/2016 PROLONG 2022	<p>PL 15.09.2025 Proposed text modification: Silicone decoupling ring with an inner diameter of 13,2 mm or more but no more than 17,2 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems</p> <p>-----</p> <p>Silicone decoupling ring with an inner diameter of 14,7 mm or more but not more than 16,0 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	<p>Round 2026.07 Amendment request</p> <p>Decoupling rings contribute to the manufacturing of sensors used in automotive driving assistance systems, mainly for park assist (ULS - Ultrasonic Parking Sensor). Decoupling rings provide sealing and insulating functions to protect the sensor from external vibrations.</p>
5602 10 19		2281825/2025	<p>DE 15.07.2025 Needle-punched spunbond nonwovens, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol weighing XX g/m2</p> <p>--</p> <p>NL 04.06.2025 (Accepted by TR on 17.6) Needle punched felt, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol</p> <p>--</p> <p>TR 10.06.2025 Not impregnated, coated, covered or laminated needle punched felt ,</p> <ul style="list-style-type: none"> - fibers of the felt contain polyvinyl alcohol content of 20 % or more but not more than 40 % <p>--</p> <p>NL 04.06.2025 (Accepted by TR on 17.6) Needle punched felt, consisting of polyamide fibres individually coated with polyvinylalcohol,</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	<p>Round 2026.1 to be used in the manufacture of microfiber synthetic leather</p>

			containing by weight 20 % or more but not more than 40 % of polyvinylalcohol -- Needle punched felt with a polyvinyl alcohol content of 20 % or more but not more than 40 %					
ex 8406 81 00	10	6501845/2024	DE 15.09.2025 amendment proposal: Industrial steam turbine with: - an output of 40 MW or more but not more than 90 MW, - designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C, - equipped with individually controlled single or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar ----- Industrial steam turbine with: - an output of more than 40 MW but not more than 90 MW, - designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C, - equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 amendment request Round 2025/7 used for the production of power generation units
ex 8418 99 90	40	6662970/2024	PL 15.09.2025 amendment proposal: An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: - measuring 337 x 237 x 17 mm or more, but not more than 868 x 399 x 78 mm, - with a total weight of a set of 236 g or more, but not more than 1 750 g, - with a fixed sensor, - with noise absorber,	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 amendment request Round 2025/7 for use in the manufacture of freezers or refrigerators

			<p>- with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket, for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40</p> <p>-----</p> <p>An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators:</p> <ul style="list-style-type: none"> - measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm, - with a total weight of a set of 236 g or more, but not more than 1 010 g, - with a fixed sensor, - with noise absorber, - with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket, <p>for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (1)</p>					
ex 8504 31 80	30	1195/2008 PROLONG 2019 PROLONG 2024 PROLONG 2025	<p>SK 15.09.2025 new text proposal: Transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters and goods of heading 8537. ----- ---- Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters (1)</p>	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 amendment request
ex 8507 60 00	26	6609698/2023	<p>IT 15.9.2025 new text description: Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, 	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant Applicant Applicant	Round 2026/07 request for amendment Round 2024/07 used for assembly of ion lithium electric accumulators, which will be incorporated in battery electric vehicles.

			<ul style="list-style-type: none"> - a height of 110 mm or more, but not more than 155 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh <p>-----</p> <p>Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh 					
ex 8507 60 00	33	1232310/2015	<p>Lithium-ion battery module or accumulator, with:</p> <ul style="list-style-type: none"> - a length of 150 mm or more, but not more than 1 310 mm, - a width of 100 mm or more, but not more than 1 000 mm, - a height of 200 mm or more, but not more than 1 500 mm, - a weight of 50 kg or more, but not more than 200 kg, - cells of a nominal capacity of 58 Ah or more but not more than 500Ah, - a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC 	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant Applicant Applicant Applicant Applicant	Round 2026-07: Roll-over Round 2026-01: review of the suspension/prolongation 1 year ROUND 01-2016 The product is a battery pack for use in a stationary energy storage application.
ex 8537 10 91	75	6633310/2024	HU 15.09.2025 Proposed text modification: Printed circuit board equipped with a microcontroller for operating and/or control purposes	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant Applicant	Round 2026.07 amendment request Round 2025.7 - control circuit boards for household appliances

			<ul style="list-style-type: none"> - with or without operating components, signal components and display, - for operating voltages of 5V DC or more but not more than 24V DC or 220V AC or more but not more than 400V AC, <p>for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60</p> <p>-----</p> <p>Printed circuit board equipped with a microcontroller for operating and/or control purposes</p> <ul style="list-style-type: none"> - with or without operating components, signal components and display, - for operating voltages of 5V DC or more but not more than 12V DC or 220V AC or more but not more than 400V AC, <p>for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60</p> <p>(1)</p>					
ex 8544 30 00 ex 8544 42 90	40 40	847787/2014 PROLONG 2020 PROLONG 2025	<p>HU 15.09.2025 proposed description: Wire harness or cable for steering system or motor vehicle rear-view systems:</p> <ul style="list-style-type: none"> - for an operating voltage of 12V or 24V, - with connectors on both sides, - whether or not with anchor clamps of plastic for mounting on a motor vehicle steering box <p>-----</p> <p>Wire harness or cable for steering system:</p> <ul style="list-style-type: none"> - for an operating voltage of 12 V, - with connectors on both sides, - whether or not with anchor clamps of plastic for mounting on a motor vehicle steering box 	<u>S</u>	Amendme nt	UNDER EXAMINATION	Applicant	Round 2026.07 amendment request ROUND 2015-01 Sensor harness is used to connect the torque sensor with electro- motor in belt drive steering system.

ex 8708 95 99	50	5870000/2021	<p>SK 15.09.2025 Requested amended description Airbag inflator containing pyrotechnics, whether or not cold gas, as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more</p> <p>-----</p> <p>Airbag inflator containing both pyrotechnics and cold gas as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 amendment request Round 2022/7 Hybrid inflators for production of passenger safety airbags
ex 9002 11 00	85	3076474/2014 PROLONG 2025	<p>DE 15.09.2025 new text proposal Lens with</p> <ul style="list-style-type: none"> - a horizontal field of view of 20° or more, but not more than 220°, - a focal length of 1.16 mm or more, but not more than 20 mm, - a relative aperture of f/1.2 or more, but not more than f/4, and - a diameter of 5 mm or more, but not more than 40 mm, - for use in the manufacture of CMOS vehicle-mounted cameras or IP network cameras <p>-----</p> <p>Lens assembly with:</p> <ul style="list-style-type: none"> - a horizontal field of view range of 20 deg or more, but not more than 200 deg, - a focal length of 1,16 mm or more, but not more than 20 mm, - a relative aperture of F/1,2 or more, but not more than F/4, and - a diameter of 5 mm or more, but not more than 40 mm, <p>for use in the manufacture of CMOS automotive cameras or in IP network cameras production (1)</p>	<u>S</u>	Amendment	UNDER EXAMINATION	Applicant	Round 2026.07 amendment request ROUND 2015-07 Using a camera module align assembly, the lenses are accurately aligned into the automotive camera assembly in a five axis alignment, fixed in position with an epoxy resin and they are calibrated and image tested.

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.